


Driver: _____ Date: _____
 Track: _____ Events: _____
 Condition: _____

FRONT SUSPENSIONS




Diameter of A.R.B : _____ mm
 Bumpsteer Washers : _____
 Camber angle : _____
 Toe angle : _____
 Ride Height : _____ mm


Steering rack:



Camber Links:



Shock Position:




Washers: _____

A Arm: 0 1



REAR SUSPENSIONS




Diameter of A.R.B : _____ mm
 Hub Tower : A B
 Camber angle : _____
 Toe angle : _____
 Ride Height : _____ mm
 Wheelbase : Long / Med / Short


A Arm:



Camber Links:



Shock Position:



Washers: _____

FRONT SHOCKS

Spring: _____ Piston: _____
 Shock oil: _____ Limiter: _____

REAR SHOCKS

Spring: _____ Piston: _____
 Shock oil: _____ Limiter: _____

Shocks: AE / Losi / Kyosho / Tamiya / Durango / Other

DIFFERENTIALS

Front Diff setting: _____
 Rear Diff setting: _____

AERO DEVICE

Body : _____ Rear Wing: _____
 Wing Angle : _____ Front Wing: _____

FRONT TIRES

Tire / Compound: _____
 Insert: _____ Wheel: _____

REAR TIRES

Tire / Compound: _____
 Insert: _____ Wheel: _____

ELECTRONICS

Motor: _____ ESC: _____
 Pinion / Spur : T / T Servo: _____

Radio: _____ Receiver: _____
 ESC Setting: _____

TRACK INFO

Traction: High / Midium / Low Somooth / Bumpy SoftDirt / Grass / Clay / Astroturf Dry / Wet Dusty / Clean